

STAR RNP1 RWY 15 (ATC DISCRETION) DESCRIPTION

FOSQA 1Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	FOSQA	-	-	-	-	-	+FL110	-	RNP1
TF	LONDA	-	138° (139.9°)	-	18.2	-	+4500	-	RNP1

BERMI 1Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BERMI	-	-	-	-	-	-	-	RNP1
TF	PEKOD	-	020° (021.9°)	-	13.7	-	+6000	-	RNP1
TF	DEDRA	-	032° (034.5°)	-	9.9	-	+4500	-	RNP1
TF	RCA	-	011° (012.9°)	-	13.7	-	+4500	-	RNP1
TF	CR404	-	013° (015.4°)	-	5.5	-	+4500	-	RNP1
TF	CR402	-	013° (015.4)	-	4.5	-	+4500	-210Kt	RNP1
TF	CR403	-	336° (338°)	-	5.0	-	+4500	-210Kt	RNP1
TF	LONDA	-	246° (248.1°)	-	6.0	-	+4500	-	RNP1

STAR RNP1 RWY 33 (ATC DISCRETION) DESCRIPTION

BERMI 1E

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BERMI	-	-	-	-	-	-	-	RNP1
TF	PEKOD	-	020° (021.9°)	-	13.7	-	+6000	-	RNP1
TF	EKTEM	-	017° (108.6°)	-	11.2	-	+4000	-	RNP1

BERMI 1T

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BERMI	-	-	-	-	-	-	-	RNP1
TF	PEKOD	-	020° (021.9°)	-	13.7	-	+6000	-	RNP1
TF	DEDRA	-	032° (034.5°)	-	9.9	-	+3000	-	RNP1

FOSQA 1E

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	FOSQA	-	-	-	-	-	+FL110	-	RNP1
TF	CR406	-	150° (151.8°)	-	15.2	-	+4000	-	RNP1
TF	CR401	-	150° (151.8°)	-	11.2	-	+4000	-	RNP1
TF	CR703	-	182° (184.1°)	-	8.7	-	+4000	-	RNP1
TF	EKTEM	-	182° (184.1°)	-	5.0	-	+4000	-	RNP1

Holding RNAV

Path Terminator	Waypoint Identifier	Inbound Course °M(°T)	Leg Distance (NM) (1)	Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	LONDA	156° (158°)	N.A.	4.2	L	+4500	-	-200	2.1	RNAV1
HM	DEDRA	017° (019°)	N.A.	4.1	R	+3000	6000	-200	2.1	RNAV1
HM	EKTEM	023° (025°)	N.A.	3.8	L	+4000	FL190	-185	2.1	RNAV1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

WAYPOINT LIST

Waypoint Identifier	Coordinates
CR401	38°07'20.79" 015°33'31.70"E
CR402	38°14'14.79"N 015°42'4.55"E
CR403	38°18'53.27"N 015°39'41.91"E
CR404	38°09'53.68"N 015°40'33.56"E
CR406	38°17'13.31" N 015°26'51.18"E
CR703	37°58'41.62"N 015°32'44.31"E