

STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO

JEDDAH/King Abdulaziz Intl(OEJN)

RNAV RWY 34R

VEMEM 1C MISAM 1C MUVOL 1C NOMDA 1C
BOSUT 2N EGMEG 2N IMDAP 2N ULULU 2N
VEMEM 2N MISAM 2N MUVOL 2N NOMDA 2N

TABULAR DESCRIPTION

RNAV RWY 34R											
Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (°/ft)	Navigation Specification
EGMEG 2N ARRIVAL											
010	IF	EGMEG	-	-	-	-	-	-	-	-	RNAV 1
020	TF	JN910	-	028(031.6)	-3.8	7.1	-	-FL170	-	-	RNAV 1
030	TF	ULULU	-	028(031.6)	-3.8	32.9	-	+13000	-	-	RNAV 1
040	TF	JN917	-	041(045.2)	-3.8	10.7	-	+10000	@210	-	RNAV 1
050	TF	JN920	-	066(069.8)	-3.8	6.3	-	+8000	-	-	RNAV 1
060	TF	ASVAK	-	066(069.8)	-3.8	6.8	R	-	-	-	RNAV 1
070	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
080	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
090	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
100	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
110	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
120	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1
IMDAP 2N ARRIVAL											
010	IF	IMDAP	-	-	-	-	-	-	-	-	RNAV 1
020	TF	OBTUG	-	241(244.5)	-3.8	17.3	L	+9000	@210	-	RNAV 1
030	TF	PUSPO	-	156(159.8)	-3.8	6.0	-	+7000	-	-	RNAV 1
040	TF	ASVAK	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
060	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
070	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
080	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
090	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
100	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1
ULULU 2N ARRIVAL											
010	IF	ULULU	-	-	-	-	-	-	-	-	RNAV 1
020	TF	JN917	-	041(045.2)	-3.8	10.7	-	+10000	@210	-	RNAV 1
030	TF	JN920	-	066(069.8)	-3.8	6.3	-	+8000	-	-	RNAV 1
040	TF	ASVAK	-	066(069.8)	-3.8	6.8	R	-	-	-	RNAV 1
050	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
060	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
070	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
080	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
090	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
100	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1
VEMEM 2N ARRIVAL (Use on ATC instruction only)											
010	IF	VEMEM	-	-	-	-	-	-	-	-	RNAV 1
020	TF	RABTU	-	233(236.8)	-3.8	10.0	L	+FL170	@250	-	RNAV 1
030	TF	JN799	-	150(153.6)	-3.8	6.0	-	-	-	-	RNAV 1
040	TF	JN797	-	164(167.4)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	RABEP	-	177(181.2)	-3.8	6.1	R	+FL170	@250	-	RNAV 1
060	TF	IMDAP	-	274(278.2)	-3.8	25.0	-	+FL150	-	-	RNAV 1
070	TF	OBTUG	-	241(244.5)	-3.8	17.3	L	+9000	@210	-	RNAV 1
080	TF	PUSPO	-	156(159.8)	-3.8	6.0	-	+7000	-	-	RNAV 1
090	TF	ASVAK	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
100	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
110	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
120	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
130	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
140	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
150	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1

CHANGE: Table updated

AMDT: Original, 10 AUG 23

ICAO PANS OPS