

Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	RESA dimensions (m)	Description, location of arresting system	OFZ
7	8	9	10	11	12	13
see AOC	-	60 x 150	2290 x 300	90 x 90	-	-
see AOC	-	60 x 150	2290 x 300	240 x 90	-	Available

Remarks	
14	
07	Nil
25	Nil

EDDG AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
07 TWY C	2170 1285	2230 1345	2170 1285	2170 NIL
25 TWY C	2170 890	2230 950	2170 890	1970 NIL

Remarks	
6	
07	Nil
25	Nil

EDDG AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
07	ALSAF LIH 420 m Sequence flash available	G LIH	3.0° 50.00 ft	-	Up to 1270 m: W LIH, 1270 – 1870 m: R/W LIH, 1870 – 2170 m: R LIH. 15 m spacing	W LIH	R LIH	-
25	ALSAF LIH Sequence flash available	G LIH	3.0° 51.00 ft	W LIH	Up to 1070 m: W LIH, 1070 – 1670 m: R/W LIH, 1670 – 1970 m: R LIH. 15 m spacing	W LIH	R LIH	-

Remarks	
10	
07	Precision approach CAT I no capacitor discharge lights 300 m from THR.
25	Precision approach CAT I no capacitor discharge lights 300 m from THR.