

STANDARD ARRIVAL
ROUTES-INSTRUMENT (STAR)
RNAV (GPS, DME/DME, DME/DME/IRU)

LEIPZIG/HALLE
RWY 08L/08R

GOXLI ONE ROMEO

GOXLI 1R

Procedure Remark

Maintain downwind track beyond endpoint if no succeeding instruction (vector / clearance for approach) is received.
RCF: see chart.

Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	Recommended Navaid	NAV Specification	Remarks
IF	GOXLI	N 51 06 43.17 E 011 33 30.36	-	-	-	-	-	-	-	-	RNAV-1	-
TF	DP470	N 51 07 12.55 E 011 42 52.82	-	(T085.2) 082	5.9	-	-	-	-	-	RNAV-1	-
TF	DP471	N 51 07 31.96 E 011 49 12.78	-	(T085.3) 082	4.0	-	-	-	-	-	RNAV-1	-
TF	DP472	N 51 07 52.64 E 011 56 05.50	-	(T085.4) 082	4.3	-	-	-	-	-	RNAV-1	-
TF	DP473	N 51 08 11.31 E 012 02 25.38	-	(T085.5) 082	4.0	-	-	-	-	-	RNAV-1	-
TF	DP474	N 51 08 51.54 E 012 16 29.51	-	(T085.6) 082	8.9	-	-	-	-	-	RNAV-1	-
TF	DP475	N 51 09 10.07 E 012 23 11.18	-	(T085.8) 083	4.2	-	-	-	-	-	RNAV-1	-
TF	DP476	N 51 09 29.81 E 012 30 28.68	-	(T085.8) 083	4.6	-	-	-	-	-	RNAV-1	-
TF	DP466	N 51 15 28.66 E 012 29 48.12	-	(T355.9) 353	6.0	-	-	-	-	-	RNAV-1	-
TF	DP465	N 51 15 08.88 E 012 22 29.67	-	(T265.9) 263	4.6	-	-	-	-	-	RNAV-1	-
TF	DP464	N 51 14 50.30 E 012 15 47.12	-	(T265.8) 263	4.2	-	-	-	-	-	RNAV-1	-
TF	DP453	N 51 17 09.37 E 012 01 18.98	-	(T284.4) 281	9.4	-	-	-	-	-	RNAV-1	-
TF	DP452	N 51 16 50.64 E 011 54 57.86	-	(T265.6) 262	4.0	-	-	-	-	-	RNAV-1	-
TF	DP451	N 51 16 29.89 E 011 48 03.80	-	(T265.5) 262	4.3	-	-	-	-	-	RNAV-1	-
TF	DP450	N 51 16 10.42 E 011 41 42.60	-	(T265.4) 262	4.0	-	-	-	-	-	RNAV-1	-
FM	-	-	-	(T265.4) 262	-	-	-	-	-	LEG	RNAV-1	-

YAWOY ONE ROMEO

YAWOY 1R

Procedure Remark

Maintain downwind track beyond endpoint if no succeeding instruction (vector / clearance for approach) is received.
RCF: see chart.

Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	Recommended Navaid	NAV Specification	Remarks
IF	YAWOY	N 51 10 19.16 E 012 49 30.66	-	-	-	-	-	-	-	-	RNAV-1	-
TF	DP466	N 51 15 28.66 E 012 29 48.12	-	(T292.8) 290	13.4	-	-	-	-	-	RNAV-1	-
TF	DP465	N 51 15 08.88 E 012 22 29.67	-	(T265.9) 263	4.6	-	-	-	-	-	RNAV-1	-
TF	DP464	N 51 14 50.30 E 012 15 47.12	-	(T265.8) 263	4.2	-	-	-	-	-	RNAV-1	-
TF	DP453	N 51 17 09.37 E 012 01 18.98	-	(T284.4) 281	9.4	-	-	-	-	-	RNAV-1	-
TF	DP452	N 51 16 50.64 E 011 54 57.86	-	(T265.6) 262	4.0	-	-	-	-	-	RNAV-1	-
TF	DP451	N 51 16 29.89 E 011 48 03.80	-	(T265.5) 262	4.3	-	-	-	-	-	RNAV-1	-
TF	DP450	N 51 16 10.42 E 011 41 42.60	-	(T265.4) 262	4.0	-	-	-	-	-	RNAV-1	-
FM	-	-	-	(T265.4) 262	-	-	-	-	-	LEG	RNAV-1	-

RNAV HOLDING IDENTIFICATION

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Speed Limit (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	GOXLI	N 51 06 43.17 E 011 33 30.36	(T 085.2) 082	230-	FL080+	1 MIN	R	-
HM	YAWOY	N 51 10 19.16 E 012 49 30.66	(T 266.2) 263	230-	FL080+	1 MIN	L	-