



LOC I-BLV 109.9	APP CRS 319°	Rwy ldg TDZE Apt Elev
		7822 439 459

ILS or LOC RWY 32L

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)

DME required.	ALSIF-1	MISSED APPROACH: Climb to 1500 then climbing left turn to 2400 direct SKE TACAN and on SKE R-139 to TIBLY INT/ SKE 14.1 DME and hold.
For inop ALS, increase S-ILS 32L Cat E visibility to RVR 4000 and increase S-LOC 32L Cat C/D/E visibility to 1½ SM. Procedure turn NA for Cat E aircraft. DME from SKE TACAN. Simultaneous reception of I-BLV and SKE DME required. *RVR 1800 authorized with use of FD or AP or HUD to DA.		

ATIS ★ 128.7 256.7	ST LOUIS APP CON 125.2 281.5	SCOTT TOWER 128.25 253.5	GND CON 119.2 275.8	CLNC DEL 119.875 263.025
------------------------------	--	------------------------------------	-------------------------------	------------------------------------



1500	2400	SKE	SKE R-139	TIBLY INT	BVIL SKE (6.7)	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50). Remain within 10 NM
1.4 NM	4.6 NM					
CATEGORY	A	B	C	D	E	
S-ILS 32L *	639/24 200 (200-½)					
S-LOC 32L	920/24 481 (500-½)		920/50 481 (500-1)			
CIRCLING	1000-1 541 (600-1)	1120-1 661 (700-1)	1240-2¼ 781 (800-2¼)	1240-2½ 781 (800-2½)	1240-2¾ 781 (800-2¾)	