



RNAV SID RWY 03

EBEBU 1C OGLOB 1C SOTUP 1C

DME/DME OPS: NOT SUPPORTED

ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART

SQUAWK: WHEN LINING UP SQUAWK THE ASSIGNED CODE

INITIAL CLIMB: MNM TURNING ALTITUDE ACCORDING TO RTE CODING.
PDG 3.7 % (225 FT/NM) UNTIL 230 FT.
CLOSE-IN OBSTACLES EXIST, SEE EFMA AD 2.10 - 5

NOISE ABATEMENT: AFTER TAKE-OFF CLIMB AS RAPIDLY AS PRACTICABLE TO AT LEAST 2000 FT ABOVE AD ELEV
PUBLISHED SID ROUTES ARE ALSO MINIMUM NOISE ROUTINGS

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

CHG: new PROC

EFMA RNAV SID RWY 03										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
EBEBU 1C RNAV 1	010	CA	-	-	016°	023.4°T	-		A580+	
	020	DF	ADTUC	-	-	-	-			K180-
	030	TF	URZUP	-	106°	113.4°T	5.0			
	040	TF	EBEBU	-	106°	113.7°T	11.0			

OGLOB 1C RNAV 1	010	CA	-	-	016°	023.4°T	-		A580+	
	020	DF	ADTUC	-	-	-	-			K180-
	030	TF	FUSCE	-	286°	293.4°T	5.0	L		K210-
	040	TF	OGLOB	-	203°	210.4°T	21.0			

SOTUP 1C RNAV 1	010	CA	-	-	016°	023.4°T	-		A580+	
	020	DF	ADTUC	-	-	-	-			K180-
	030	TF	SOTUP	-	067°	074.8°T	20.3			

WPT COORD	
SEE PAGE EFMA AD 2.15 - 1	