

**LAMPEDUSA**  
**STAR RNP1 RWY 08**

**LICDE 1A**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LICDE	-	-	-	-	-	+6500 (*)	-250	RNP 1
TF	CD303	-	213 (216.3)		17.9		+3000	-210	RNP 1
TF	CD304	-	168 (170.4)		6.0		+2000	-200	RNP 1
TF	MUPOC	-	078 (080.4)		5.0		+2000	-200	RNP 1

(\*) +FL65 or TRNSITION LEVEL if higher

**LUZOT 1A**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LUZOT	-	-	-	-	-	+6500 (*)	-250	RNP 1
TF	BUBEC	-	212 (214.8)	-	20.1	-	+4000	-250	RNP 1
TF	CD313	-	258 (260.7)	-	24.8	-	+4000	-210	RNP 1
TF	CD304	-	348 (350.4)	-	9.1	-	+2000	-200	RNP 1
TF	MUPOC	-	078 (080.4)	-	5.0	-	+2000	-200	RNP 1

(\*) +FL65 or TRNSITION LEVEL if higher

**BUBEC 1A (Following Missed Approach RWY08)**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BUBEC	-	-	-	-	-	+2000	-250	RNP 1
TF	CD313	-	258 (260.7)	-	24.8	-	+2000	-210	RNP 1
TF	CD304	-	348 (350.4)	-	9.1	-	+2000	-200	RNP 1
TF	MUPOC	-	078 (080.4)	-	5.0	-	+2000	-200	RNP 1

**STAR RNP1 RWY 26**

**EMCOL 1C**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	EMCOL	-	-	-	-	-	+6500 (*)	-250	RNP 1
TF	CD323	-	144 (147.0)	-	14.4	-	-4000/+2000	-210	RNP 1
TF	CD324	-	168 (170.8)	-	5.0	-	-4000/+2000	-200	RNP 1
TF	BOLFU	-	258 (260.8)	-	2.1	-	-4000/+2000	-200	RNP 1

(\*) +FL65 or TRNSITION LEVEL if higher

**LUZOT 1C**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LUZOT	N	-	-	-	-	+6500 (*)	-250	RNP 1
TF	CD324	N	229 (231.9)	-	11.0	-	+2000	-200	RNP 1
TF	BOLFU	N	258 (260.8)	-	2.1	-	+2000	-200	RNP 1

(\*) +FL65 or TRNSITION LEVEL if higher

**LPD 1C**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LPD	N	-	-	-	-	+6500 (*)	-250	RNP 1
TF	CD331	N	043 (045.5)	-	8.7	-	+2000	-230	RNP 1
TF	CD323	N	078 (080.7)	-	5.0	-	+2000	-210	RNP 1
TF	CD324	N	168 (170.8)	-	5.0	-	+2000	-200	RNP 1
TF	BOLFU	N	258 (260.8)	-	2.1	-	+2000	-200	RNP 1

(\*) +FL65 or TRNSITION LEVEL if higher

**HOLDING RNAV1**

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	MUPOC	078 (080.4)	3.3	-/4.2	R	+2000	-	190	+3.0	RNAV1
HM	BOLFU	258 (260.8)	3.3	- / 4.2	L	+2000	-	190	+3.0	RNAV1
HM	BUBEC	307 (310.1)	3.3	-/4.2	L	+2000 (3)	-	190	+3.0	RNAV1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

(3) Maximum Holding altitude 3000Ft

**WAYPOINT LIST**

Waypoint Identifier	Coordinates
CD303	35° 33' 06.13"N 012° 16' 08.33"E
CD304	35° 27' 10.75"N 012° 17' 21.81"E
CD313	35° 18' 11.40"N 012° 19' 12.93"E
CD323	35° 36' 52.89"N 012° 51' 29.65"E
CD324	35° 31' 56.34"N 012° 52' 28.65"E
CD331	35° 36' 04.51"N 012° 45' 26.57"E