

Initial climb (CAT A-B-C) description

After take-off proceed on TR 312° until PO601, then turn right to join the assigned SID.

Minimum climb gradient:

- 334 ft/NM (5.5%) until passing 6000 ft due to obstacles;
- 365 ft/NM (6.0%) until passing FL90 (8.2% until passing FL 110 for SID EXFIN 7B) for ATC reasons.

Execute the turn with:

- 20° minimum bank angle;
- IAS MAX 175 KT

SID RNAV 1 RWY 32 (CAT A-B-C) description

Initial climb procedure executed:

ADXEF 7A

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	ADXEF	-	103°	-	31.7	-	+FL95	-	RNAV1

AFNEW 7A (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	AFNEW	-	144°	-	42.5	-	+FL130	-	RNAV1

EXFIN 7B

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	PO611	-	070°	-	9.9	-	+FL110	-	RNAV1
TF	EXFIN	-	070°	-	8.9	-	-	-	RNAV1

OSBUL 7B

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	PO603	-	222°	-	8.3	R	-	- 220	RNAV1
TF	OSBUL	-	184°	-	28.6	L	+FL90	- 220	RNAV1

OSKOR 7U

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	PO603	-	222°	-	8.3	R	-	- 220	RNAV1
TF	PO604	-	261°	-	15.5	R	-	- 220	RNAV1
TF	OSKOR	-	007°	-	23.4	R	+FL110	- 220	RNAV1

PIQUZ 7A (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	PIQUZ	-	123°	-	36.0	-	+FL95	-	RNAV1

UVNIB 1U (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 175	RNAV1
DF	PO602	-	-	-	-	R	+6000	- 175	RNAV1
TF	PO603	-	222°	-	8.3	R	-	- 220	RNAV1
TF	PO604	-	261°	-	15.5	R	-	- 220	RNAV1
TF	UVNIB	-	261°	-	20.3	-	+FL90	-	RNAV1

Waypoints Table formatted according ARINC 424 standards

Waypoint	Latitude	Longitude
PO601	N45274437	E010170028
PO602	N45233274	E010310813
PO603	N45174094	E010224682
PO604	N45155688	E010005760
PO611	N45262890	E010443703