



**RNAV STAR RWY 07**

ARLOM 1E NAXEP 1E OTKAP 1E VEHUF 1E

- |                  |  |  |  |
|------------------|--|--|--|
| DME/DME OPS:     | NOT SUPPORTED  | RCF:                                       | SELECT TRANSPONDER CODE 7600                                   |
| ROUTES:          | RNAV PROC CODING ON THE VERSO OF THE CHART<br>ATC WILL GIVE DESCENT CLEARANCES                       | RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED: | FOLLOW THE STAR TO THE RESPECTIVE RWY AND EXECUTE IAP AND LAND |
| WPT CONSTRAINTS: | ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC | DURING RADAR VECTURING BEFORE IAF:         | IN ACCORDANCE WITH THE RULES OF THE AIR                        |
| CD OPS:          | BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR  | AREA MNM ALT:                              | SEE AMA INDEX, AIP ENR 6.1 - 3                                 |
| NOISE ABATEMENT: | AVOID OVERFLYING THE CITY OF KOUVOLA BELOW 2000  |  |  |

CHG: radio data

EFUT RNAV STAR RWY 07										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
ARLOM 1E RNAV 1	010	IF	ARLOM	-	-	-	-	F100+		
	020	TF	ELSUW	-	264°	274.2°T	22.3			
	030	TF	ATVAP	-	248°	258.1°T	10.5	A2300+		K240-
	040	TF	ULNAV	-	338°	347.8°T	5.0	A2300+		

NAXEP 1E RNAV 1	010	IF	NAXEP	-	-	-	-	F100+		
	020	TF	SUZCU	-	177°	186.9°T	3.5	A2300+		K240-
	030	TF	ULNAV	-	147°	157.0°T	4.5	A2300+		

OTKAP 1E RNAV 1	010	IF	OTKAP	-	-	-	-	F100+		
	020	TF	EPATU	-	219°	229.5°T	6.4			
	030	TF	POWUQ	-	248°	258.3°T	9.6			
	040	TF	USIMI	-	248°	258.0°T	10.5	A2300+		K240-
	050	TF	ULNAV	-	157°	167.7°T	5.0	A2300+		

VEHUF 1E RNAV 1	010	IF	VEHUF	-	-	-	-	F100+		
	020	TF	ULNAV	-	059°	069.0°T	15.2	A2300+		

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM		
ULNAV	347.8°T	338°	Right	K230-	A2300	1 MIN	-		

WPT COORD
SEE PAGE EFUT AD 2.15 - 1