

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
09R	ALSAF LIL_LIH Sequence flash available	G LIH	3.0° 65.00 ft	-	W LIH spacing 30 m	Up to 1740 m: W LIH; 1740 - 2340 m: Y LIH. Spacing 60 m.	R LIH	-
27L	ALSAF LIL_LIH Sequence flash available	G LIH	3.0° 55.00 ft	-	W LIH spacing 30 m	Up to 1740 m: W LIH; 1740 - 2340 m: Y LIH. Spacing 60 m.	R LIH	-

Remarks	
	10
09C	Nil
27C	Nil
09L	Nil
27R	Nil
09R	LED lights used for the runway threshold lights. LED lights used for the sequenced flashing lights.
27L	LED lights used for the runway end lights. LED lights used for the sequenced flashing lights.

EDDV AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDDV 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs A, A1, A2, B, C, D, E, F, G, H, J, K, KTO, L, M, N, Q: B LIL TWY Center line lights of TWYs G, H, KTO, L, M, N: G LIH (Y/G colour-coded for exit) TWY Center line lights of TWY F: G LIH
4	Secondary power supply including switch-over time	Available / < 1 SEC
5	Remarks	Nil