

Roma Fiumicino RNP RWY 34R – Instrument Approach procedure via NEVUX

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH	Navigation Specification
010	IF	NEVUX	-	-	-	-	-	+3500	-	-	RNAV1
020	TF	ENEXU	-	010°(013.4°)	-	6.0	-	+3000	-	-	RNP APCH
030	TF	RF733	-	339°(342.7°)	-	4.2	-	+2500	-	-	RNP APCH
040	TF	RW34R	Y	339°(342.7°)	-	7.7	-	@ 63	-	3°/17.5M	RNP APCH
050	CF	RF735	Y	339°(342.7°)	3.4°E	11.9	-	+2000	-	-	RNP APCH
060	DF	CMP	-	-	-	-	R	+4000	- 185	-	RNAV1
070	HM	CMP	Y	207°(210.1°)	3.4°E	-	R	+4000	- 185	-	RNAV1

Roma Fiumicino RNP RWY 34R – Instrument Approach procedure via ODULA

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH	Navigation Specification
010	IF	ODULA	-	-	-	-	-	+3500	-	-	RNAV1
020	TF	ENEXU	-	339°(342.7°)	-	5.0	-	+3000	-	-	RNP APCH
030	TF	RF733	-	339°(342.7°)	-	4.2	-	+2500	-	-	RNP APCH
040	TF	RW34R	Y	339°(342.7°)	-	7.7	-	@ 63	-	3°/17.5M	RNP APCH
050	CF	RF735	Y	339°(342.7°)	3.4°E	11.9	-	+2000	-	-	RNP APCH
060	DF	CMP	-	-	-	-	R	+4000	- 185	-	RNAV1
070	HM	CMP	Y	207°(210.1°)	3.4°E	-	R	+4000	- 185	-	RNAV1

Path Terminator	Waypoint Name	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Performance
HM	NEVUX	339 (342.0)	4.0	-/5.5	L	2500	-	- 200	3.4°E	RNAV1
HM	ODULA	339 (342.0)	4.0	-/5.5	R	2500	-	- 200	3.4°E	RNAV1
HM	CMP	207° (210.1°)	-	- / 4.3	R	4000	-	- 185	3.4°E	RNAV 1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

**WAYPOINT LIST
RNP RWY34R**

Waypoint Identifier	Coordinates
RF733	41°41'26.3N 012°19'34.9E
RF735	42°00'04.9N 012°11'46.6E

SBAS FAS DATA BLOCK LIRF RNP RWY 34R
Input data

Operation Type	0
SBAS Provider	1
Airport Identifier	LIRF
Runway	34
Runway Direction	1
Approach Performance Designator	0
Route Indicator	
Reference Path Data Selector	0
Reference Path Identifier	E34A
LTP/FTP Latitude	414844.7950N
LTP/FTP Longitude	0121631.8910E
LTP/FTP Ellipsoidal Height (metres)	49.8
FPAP Latitude	415048.7245N
Delta FPAP Latitude (seconds)	123.9295
FPAP Longitude	0121540.0265E
Delta FPAP Longitude (seconds)	-51.8645
Threshold Crossing Height	57.4
TCH Units Selector	0
Glidepath Angle (degrees)	3.00
Course Width (metres)	105.00
Length Offset (metres)	104
HAL (metres)	40.0
VAL (metres)	50.0

Output data

Data Block	10 06 12 09 0C 62 00 00 01 34 33 05 F6 A6 F1 11 26 A1 44 05 F2 15 33 C8 03 CF 6A FE 3E 02 2C 01 64 0D C8 FA 83 E1 02 1D
Calculated CRC Value	83E1021D