

MEMMINGEN  
RWY 24

INSTRUMENT APPROACH PROCEDURE  
TABULAR DESCRIPTION  
RNP

**Procedure Remarks**

1. PROCEDURE NOT TO BE USED DURING ACTIVITY OF NLF5.
2. EGNOS CH 78870 E24A.

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) / (Mag Track°)	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from JA438	IF	JA438	N 48 04 42.34 E 010 27 58.20	N	-	-	-	A4000+	-	-	RNP APCH	-
	TF	TUXNE	N 48 02 40.16 E 010 22 48.96	N	(T 239.5) 237	4.0	-	A4000+	-	-	RNP APCH	-
Initial APCH from ALG	IF	ALG	N 47 59 50.57 E 010 15 43.88	N	-	-	-	A6000+	-	-	RNP APCH	-
	TF	JA456	N 47 57 31.29 E 010 27 21.58	N	(T 106.5) 104	8.2	-	A6000+	-	-	RNP APCH	-
	TF	JA458	N 47 59 32.47 E 010 32 29.21	N	(T 059.6) 057	4.0	-	A5000+	-	-	RNP APCH	-
	TF	JA438	N 48 04 42.34 E 010 27 58.20	N	(T 329.6) 327	6.0	-	A4000+	210-	-	RNP APCH	-
	TF	TUXNE	N 48 02 40.16 E 010 22 48.96	N	(T 239.5) 237	4.0	-	A4000+	-	-	RNP APCH	-
APCH	TF	RW24	N 47 59 39.46 E 010 15 11.95	Y	(T 239.5) 237	5.9	-	-	-	-3.0/57	RNP APCH	-
Missed APCH	CF	JA248	N 47 56 38.25 E 010 07 36.36	Y	(T 239.4) 237	5.9	-	-	-	-	RNP APCH	-
	DF	ALG	N 47 59 50.57 E 010 15 43.88	N	-	-	L	@A6000	230-	-	RNP APCH	-

**RNAV HOLDING IDENTIFICATION**

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) / (Mag Track°)	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time (MIN) / Distance outbound	Turn Direction	Remarks
HM	ALG	N 47 59 50.57 E 010 15 43.88	(T 149.4) 147	230-	A6000+	1 MIN	L	-