

FRANKFURT MAIN

INSTRUMENT APPROACH PROCEDURE

RNP X RWY 25L

TABULAR DESCRIPTION

Procedure Remark:												
Approach Segment	Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / FL	Speed Limit / (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV - Specification	Remarks
Initial APCH from KUGUK	IF	KUGUK	N 49 57 57.76 E 009 01 15.37	N	-	-	-	A5000+	-	-	RNP APCH	-
	TF	DF907	N 50 00 52.03 E 008 57 56.67	N	(T323.7) 320	3.6	-	A4200+	-	-	RNP APCH	-
	TF	DF901	N 50 03 37.88 E 008 52 09.99	N	(T306.6) 303	4.6	-	A3000+	-	-	RNP APCH	-
Initial APCH from ORVIV	IF	ORVIV	N 50 10 59.99 E 009 00 46.36	N	-	-	-	A5000+	-	-	RNP APCH	-
	TF	DF902	N 50 05 05.64 E 008 59 00.09	N	(T190.9) 188	6.0	-	A3900+	-	-	RNP APCH	-
	TF	DF901	N 50 03 37.88 E 008 52 09.99	N	(T251.7) 248	4.6	-	A3000+	-	-	RNP APCH	-
APCH	TF	TITUT	N 50 04 07.82 E 008 42 26.99	N	(T274.6) 271	6.3	-	A2000+	-	-	RNP APCH	FAF for coding
	TF	RW25L	N 50 02 24.19 E 008 35 11.51	Y	(T249.7) 246	5.0	-	-	-	-3.0/50	RNP APCH	-
Missed APCH	DF	DF290	N 50 01 13.69 E 008 30 16.69	Y	-	-	-	-	220-	-	RNP APCH	-
	DF	DF685	N 49 58 07.58 E 008 21 57.70	N	-	-	-	-	220-	-	RNP APCH	-
	CA	-	-	-	(T240.0) 237	-	-	A5000+	220-	-	RNP APCH	-
	DF	CHA	N 49 55 15.97 E 009 02 23.34	N	-	-	L	@A5000	250-	-	RNP APCH	-
RNAV HOLDING IDENTIFICATION												
Path Terminator		Holding Fix	Coordinates	(True Track°) Mag Track°	Time (MIN) / Distance outbound	Turn Direction	Altitude (ft) / FL	Speed Limit (kt IAS)		Remarks		
HM		CHA	N 49 55 15.97 E 009 02 23.34	(T286.5) 283	1	R	FL100-A5000+	230-		-		