

STANDARD DEPARTURE
ROUTES – INSTRUMENT
(SID)

MANNHEIM CITY
RWY 09

| Designator | Route | After Take-Off | | Remarks |
|-----------------|--|----------------|-------------------------|--|
| | | Climb to | Contact | |
| 1 | 2 | 3 | 4 | 5 |
| MANEM 8C | MANEM EIGHT CHARLIE On track 091° to 3.0 DME MND; RT, on bearing 147° inbound NKR to 5.5 DME MND; RT, on track 209°; RT, on track 261° from NKR / R081 ZWN to MANEM (Δ). Climb with 4.0% (243 ft/NM) or more until passing 600. GPS/FMS RNAV: [A800+] - FM040[R] - FM041[R] - FM043[R] - MANEM. | 5000 ft | Langen Radar 129.355 | 1. PDG 4.0% (243 ft/NM) due to obstacles. 2. During activity of ED-R 205 (TRA) MAX FL80. |
| OLIVI 6C | OLIVI SIX CHARLIE On track 091° to 3.0 DME MND; RT, on bearing 147° inbound NKR to 5.5 DME MND; RT, on track 209°; RT, on track 296° from NKR to 7.8 DME MND; RT, on track 333° to KOSAX (Δ); LT, on track 294° to OLIVI (Δ). Climb with 4.0% (243 ft/NM) or more until passing 600. GPS/FMS RNAV: [A800+] - FM040[R] - FM041[R] - FM042[R] - FM045[R] - KOSAX[A6000+; L] - OLIVI. | | | 1. PDG 4.0% (243 ft/NM) due to obstacles. 2. After 7.8 DME MND BRNAV equipment necessary 3. During activity of ED-R 205 (TRA) MAX FL80. |
| RINEX 3C | RINEX THREE CHARLIE On track 091° to 3.0 DME MND; RT, on bearing 147° inbound NKR to 25.5 DME RID; RT, on track 262° from NKR to RINEX (Δ). Climb with 4.0% (243 ft/NM) or more until passing 600. Cross RINEX at 5000 or above. GPS/FMS RNAV: [A800+] - FM040[R] - FM044[R] - FM046 - RINEX[A5000+]. | | | 1. PDG 4.0% (243 ft/NM) due to obstacles. 2. PDG 5.3% (320 ft/NM) due to airspace structure. |
| ROLSO 3C | ROLSO THREE CHARLIE On track 091° to 3.0 DME MND; RT, on bearing 147° inbound NKR to 25.5 DME RID; LT, on bearing 085° from NKR to ROLSO (Δ). Climb with 4.0% (243 ft/NM) or more until passing 600. GPS/FMS RNAV: [A800+] - FM040[R] - NKR[L] - ROLSO. | | | 1. PDG 4.0% (243 ft/NM) due to obstacles. 2. Flights with destination EDDF or EDFE shall file ROLSO DCT SUPIX - T163 - PSA. |
| UMDAS 3C | UMDAS THREE CHARLIE On track 091° to 3.0 DME MND; RT, on bearing 147° inbound NKR to 25.0 DME RID; LT, on track 060° to UMDAS (Δ). Climb with 4.0% (243 ft/NM) or more until passing 600, then climb with 5.3% (320 ft/NM) or more until passing 3500. GPS/FMS RNAV: [A800+] - FM040[R] - FM047[L] - UMDAS. | | | 1. PDG 4.0% (243 ft/NM) due to obstacles, PDG 5.3% (320 ft/NM) due to airspace structure. If unable to comply, request alternative instruction by ATC. 2. After 25.0 DME RID BRNAV equipment necessary. |

(Sample: FM044 fly-over waypoint)

Contact Langen Radar immediately after take-off!