

WAAS CH 40228 W16A	APP CRS 162°	Rwy Idg TDZE Apf Elev	7000 4202 4252
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 16

WORLAND MUNI (WRL)



⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -32°C (-25°F) or above 17°C (62°F). DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA with Greybull altimeter setting. When local altimeter setting not received, use Greybull altimeter setting: increase LPV DA to 4574 feet, LNAV/VNAV DA to 4616 feet, and all MDA's 140 feet; increase LPV, LNAV/VNAV and LNAV all Cats, and Circling Cat C/D visibilities ½ SM. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 9600 direct WAPSU and on track 207° to ZURNA and hold, continue climb-in-hold to 9600.

ASOS 135.475	SALT LAKE CENTER 133.25 285.6	UNICOM 123.05 (CTAF) 0
------------------------	---	----------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 41).	9600	WAPSU	ZURNA	ELEV 4252	D	TDZE 4202
	↑	✧	tr 207°			



CATEGORY	A	B	C	D
LPV DA		4452-¾	250 (200-¾)	
LNAV/VNAV DA		4494-⅞	292 (300-⅞)	
LNAV MDA	4560-1	358 (400-1)	4560-1 ⅛	358 (400-1 ⅛)
CIRCLING	4920-1	668 (700-1)	4920-1 ¾	5020-2 ½
			668 (700-1 ¾)	768 (800-2 ½)

NW-1, 20 MAR 2025 to 17 APR 2025

NW-1, 20 MAR 2025 to 17 APR 2025