

EDHK AD 2.12 Runway physical characteristics

Designations RWY NR	TRUE BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
08	82.42°	1144 x 30	32/F/C/X/T ASPH grooved	N 54 22 44.140 E 010 08 14.390	THR 98.8 ft
26	262.42°	1144 x 30	32/F/C/X/T ASPH grooved	N 54 22 48.560 E 010 09 11.279	THR 89.2 ft

Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	RESA dimensions (m)	Description, location of arresting system	OFZ
7	8	9	10	11	12	13
see AOC	-	44 x 150	1264 x 140	47 x 60	-	-
see AOC	-	100 x 150	1264 x 140	90 x 60	-	-

Remarks	
	14
08	Nil
26	Nil

EDHK AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
08	1144	1188	1144	1036
26	1036	1136	1144	1144

Remarks	
	6
08	Nil
26	44 m of paved runway strip in front of threshold 26 may be used to increase TORA, TODA and ASDA distances accordingly.

EDHK AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
08	LIH Sequence flash available	G LIH	3.0°	W LIH	-	THR – 672 m: W LIH 733 – 1100 m: Y LIH; 60 m apart	R LIH	-