

STANDARD ARRIVAL CHART –
INSTRUMENT (STAR) - ICAO

RIYADH / King Khaled Intl (OERK)
RNAV RWY 15R/15L
ORDEM 1A TATKU 1A SIVIS 1A
NAGUB 1A ORDUX 1A

050	TF	RK653	-	327 (329.9)	-3.3	7.2	-	-	-	RNAV 1
060	TF	RK639	-	327 (330.1)	-3.3	7.0	-	-	-	RNAV 1
070	TF	RK632	-	326 (329.7)	-3.3	7.0	-	-9000	-	RNAV 1
080	TF	RK625	-	326 (329.8)	-3.3	7.0	-	-	-230	RNAV 1
090	TF	RK618	-	056 (059.8)	-3.3	7.0	-	+6000	-230	RNAV 1
100	TF	RK611	-	146 (149.9)	-3.3	7.0	-	+6000	-230	RNAV 1
110	TF	RK604	-	146 (149.9)	-3.3	7.0	-	+6000	-230	RNAV 1
120	TF	RK697	-	147 (149.9)	-3.3	7.0	-	+6000	-230	RNAV 1
130	TF	RK676	-	057 (059.9)	-3.3	7.0	-	+6000	-230	RNAV 1
140	TF	RK669	-	327 (330.0)	-3.3	7.0	-	+6000	-230	RNAV 1
150	TF	RK662	-	327 (330.0)	-3.3	7.0	-	+6000	-230	RNAV 1
160	TF	RK655	-	327 (329.9)	-3.3	7.0	-	+5000	-230	RNAV 1
170	TF	PEDIR	-	327 (329.9)	-3.3	7.0	-	+5000	-230	RNAV 1
180	TF	RK641	-	326 (329.9)	-3.3	7.0	-	@5000	-210	RNAV 1
190	TF	RK634	-	056 (059.8)	-3.3	7.0	-	@5000	-210	RNAV 1
200	TF	RK627	-	146 (149.9)	-3.3	7.0	-	@5000	-210	RNAV 1
210	TF	RK621	-	147 (149.9)	-3.3	7.0	-	@5000	-210	RNAV 1

HOLDINGS									
Path Description	Waypoint Identifier	Course M°(T°)	Timing(min) Waypoint Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (NM/h)	Magnetic Variation (°)	Navigation Specification
HM	KAVUR	073 (076.0)	1.5/-	L	FL150	FL200	-250	-3.3	RNAV 1
HM	KUNEK	088 (091.1)	1.5/-	L	FL160	FL200	-250	-3.3	RNAV 1
HM	SIVON	025 (028.1)	1.5/-	L	FL160	FL200	-250	-3.3	RNAV 1

NOTE: KAVUR, KUNEK,SIVON fly-over for holding patterns only

CHANGE: NEW TABLE

Amdt: Original, 28 Nov 24

ICAO PANS OPS