

TRANSITION ALT 5000
AD ELEV 412ft

APP	119.950
TWR	121.050
ATIS	126.955

KOS / IPPOKRATIS (LGKO)
RNP1 ARRIVAL RWY 32



USINI 1M									
SeqN°	Path Terminator	Waypoint	F/O	Bearing °M (°T)	Distance (NM)	Turn Direction	Altitude (ft)	IAS (kt)	Navigation Specification
10	IF	USINI							RNP1/GNSS only
20	TF	KO322		288 (293.4)	4.7		+5000		RNP1/GNSS only
30	TF	KO323		203 (207.5)	4.3		+4000		RNP1/GNSS only
40	TF	MORIX		112 (116.5)	7.0			-200	RNP1/GNSS only

GILOS 1M									
SeqN°	Path Terminator	Waypoint	F/O	Bearing °M (°T)	Distance (NM)	Turn Direction	Altitude (ft)	IAS (kt)	Navigation Specification
10	IF	GILOS							RNP1/GNSS only
20	TF	KO321		022 (026.8)	4.4		+5000		RNP1/GNSS only
30	TF	KO323		022 (27.4)	6.2		+4000		RNP1/GNSS only
40	TF	MORIX		112 (116.5)	7.0			-200	RNP1/GNSS only

KOPAR 1M									
SeqN°	Path Terminator	Waypoint	F/O	Bearing °M (°T)	Distance (NM)	Turn Direction	Altitude (ft)	IAS (kt)	Navigation Specification
10	IF	KOPAR							RNP1/GNSS only
20	TF	LECOK		127 (132.1)	12.2		+5000		RNP1/GNSS only
30	TF	KO323		111 (116.4)	6.7		+4000		RNP1/GNSS only
40	TF	MORIX		112 (116.5)	7.0			-200	RNP1/GNSS only

HOLDING MORIX									
SeqN°	Path Terminator	Waypoint	F/O	Bearing °M (°T)	Distance (NM)	Turn Direction	Altitude (ft)	IAS (kt)	Navigation Specification
50	HM	MORIX		085 (090.0)	3.0 (*3.9)	L	+4000	-185	RNP1/GNSS only or RNAV1/GNSS only or RNP APCH
* Holding waypoint distance (only for RNAV systems without RNAV functionality)									

WAYPOINT LIST		
WAYPOINT IDENTIFICATION	LATITUDE	LONGITUDE
GILOS	36 ⁰ 29' 15.0000'' N	026 ⁰ 54' 01.2000'' E
KO323	36 ⁰ 38' 40.8000'' N	027 ⁰ 00' 01.2000'' E
KO322	36 ⁰ 42' 30.0000'' N	027 ⁰ 02' 29.4000'' E
LECOK	36 ⁰ 41' 39.8204'' N	026 ⁰ 52' 32.6816'' E
KO321	36 ⁰ 33' 09.6000'' N	026 ⁰ 56' 27.6000'' E
KOPAR	36 ⁰ 49' 49.0000'' N	026 ⁰ 41' 19.0000'' E
MORIX	36 ⁰ 35' 33.0000'' N	027 ⁰ 07' 48.0000'' E
USINI	36 ⁰ 40' 37.0000'' N	027 ⁰ 07' 54.0000'' E
ELTAK	36 ⁰ 37' 19.4326'' N	027 ⁰ 13' 32.1823'' E