

## INITIAL CLIMB PROCEDURE RWY 07 DESCRIPTION

## REMARKS

- 1) In order to reduce the noise over surrounding settlements, pilots shall comply with the MCA and, when RWY 07 is used, shall contain turns within 8.1 NM from ARP.
- 2) Pilots shall adopt a minimum climb gradient in accordance with ICAO-Annex 6 provisions for a safe obstacles overflying. Such climb gradient shall be maintained in any foreseeable circumstance.
- 3) Minimum suggested climb gradient: 300 ft/NM until passing 4000 ft.

Warning: "Close in " obstacles penetrating OIS 2.5% exist, but they were not considered for the published procedure design gradient

## OST 1E

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.8)	-	-	-	+410	-	RNAV1
CF	RF714	Y	066 (069.8)	3.3°E	-	-	+1000	-185	RNAV1
DF	OST	-	-	-	-	L	+4000	-185	RNAV1

## WAYPOINT LIST

Waypoint Identifier	Coordinates
RF714	41°49'47.88"N 012°20'35.91"E