

STAR RNAV 1/ RNP1 RWY 13/31

(ATC discretion)

REMARK

- (1) MEA 4500 FT ATC discretion
- (2) For "monitoring and alerting" reason, RNP1 specification is required in case of radar service unavailability or degradation

LUXIL 2R

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (2)
IF	LUXIL	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	BR429	-	085 (089.5)	-	22.9	-	+FL090 (1)	-	RNAV 1/ RNP 1
TF	BR418	-	086 (089.9)	-	11.5	-	+4500	-	RNAV 1/ RNP 1
TF	GODUB	-	086 (090.0)	-	5.8	-	+3000	-200	RNAV 1/ RNP 1

OKIMO 2R

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (2)
IF	OKIMO	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	BR435	-	182 (186.0)	-	10.1	-	-	-	RNAV 1/ RNP 1
TF	BR424	-	133 (137.1)	-	11.2	-	-	-	RNAV 1/ RNP 1
TF	BR420	-	133 (137.2)	-	4.0	-	+4500	-	RNAV 1/ RNP 1
TF	BR502	-	223 (227.3)	-	3.0	-	-	-200	RNAV 1/ RNP 1
TF	NOGLU	-	223 (227.2)	-	4.0	-	+3500	-200	RNAV 1/ RNP 1

HOLDING RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	GODUB (3)	133 (137)	3.0	-/-	L	+3000	-	-185	4°E	RNAV 1
HM	NOGLU (3)	313 (317)	3.3	-/3.3	R	+3500	-	-185	4°E	RNAV 1

- (1) RNAV system with holding functionality
- (2) RNAV system without holding functionality
- (3) Entry on track

WAYPOINT LIST

Waypoint Identifier	Coordinates
BR418	40°49'16.78"N - 017°37'30.41"E
BR420	40°34'51.09"N - 018°15'00.52"E
BR424	40°37'47.35"N - 018°11'26.68"E
BR429	40°49'16.03"N - 017°22'21.52"E
BR435	40°45'59.44"N - 018°01'27.30"E
BR502	40°32'48.74"N - 018°12'06.96"E