

SID RNAV1 RWY 08

DECOLLI RWY 08

- 1) Gradiente minimo di salita: 365 ft/NM (6%) fino ad attraversare:
 - a) FL 100 per LIBRO 5K
 - b) 5000 ft per NELDA 5K
 - c) 7000 ft per ALUDU 5K
 - d) FL 85 per PIMOR 5K
- 2) Gradiente minimo di salita: 486 ft/NM (8%) fino ad attraversare:
FL 120 per PEKOD 5K

NOTA

Il gradiente di salita iniziale non prende in considerazione gli ostacoli nella "close-in area" di altezza, comprensiva del MOC, inferiore a 60 m (200 ft) sull'elevazione della DER (vedere carte ostacoli ICAO e NOTAM in vigore).

TAKE OFF RWY 08

- 1) Minimum climb gradient: 365 ft/NM (6%) till passing:
 - a) FL 100 for LIBRO 5K
 - b) 5000 ft for NELDA 5K
 - c) 7000 ft for ALUDU 5K
 - d) FL 85 for PIMOR 5K
- 2) Minimum climb gradient: 486 ft/NM (8%) till passing:
FL 120 per PEKOD 5K

REMARK

Initial climb gradient doesn't take into account "close-in" obstacles lower than 60 m (200 ft), MOC included, above DER elevation (see ICAO obstacle charts and NOTAM in force).

PEKOD 5K

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA			081°(084.0°)	3			+500		RNAV 1
DF	INDAX			3			+5000	240	RNAV 1
TF	PEKOD		029°(032.0°)	3	15.6		+FL120		RNAV 1

LIBRO 5K

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA			081°(084.0°)	3			+500		RNAV 1
DF	INDAX			3			+3500	210	RNAV 1
TF	CC600		167°(170.0°)	3	5.0		+5000	210	RNAV 1
TF	CC601		260°(262.9°)	3	10.6	R	+FL85		RNAV 1
TF	GIFAN		279°(282.0°)	3	14.6		+FL120		RNAV 1
TF	LIBRO		301°(304.4°)	3	18.7				RNAV 1

NELDA 5K

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA			081°(084.0°)	3			+500		RNAV 1
DF	INDAX			3			+3500	210	RNAV 1
TF	CC600		167°(170.0°)	3	5.0		+5000	210	RNAV 1
TF	CC601		260°(262.9°)	3	10.6	R	+7000		RNAV 1
TF	CC602		276°(279.0°)	3	10.0		+FL90		RNAV 1
TF	NELDA		212°(214.8°)	3	40.7				RNAV 1

ALUDU 5K

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA			081°(084.0°)	3			+500		RNAV 1
DF	INDAX			3			+3500	210	RNAV 1
TF	ALUDU		143°(146.0°)	3	24.8		+FL100		RNAV 1

PIMOR 5K

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA			081°(084.0°)	3			+500		RNAV 1
DF	INDAX			3			+3500		RNAV 1
TF	PIMOR		077°(080.4°)	3	27.7		+FL120		RNAV 1

TRANSITION SEGMENT TO ENROUTE

BUDIN 5B

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
IF	PEKOD			3			+FL120		RNAV 1
TF	BUDIN		335°(338.14°)	3	49		+FL120		RNAV 1

Waypoint Table Formatted according ARINC 424 standards SID RWY 08

WAYPOINT	LATITUDE	LONGITUDE
INDAX	N37294700	E015172100
CC600	N37245024	E015182407
CC601	N37233800	E015050700
GIFAN	N37264186	E014471297
CC602	N37251273	E014524336
ALUDU	N37091078	E015344685
NELDA	N36514600	E014233400
LIBRO	N37371700	E014275300
PEKOD	N37430400	E015274600
PIMOR	N37342700	E015513800
BUDIN	N38283534	E015044811