

APP CRS	Rwy Idg	9487
316°	TDZE	578
	Apt Elev	599

RNAV (RNP) Z RWY 31
NASHVILLE INTL (BNA)

T For uncompensated Baro-VNAV systems, procedure NA below -1.6°C (4°F) or above 54°C (130°F). GPS required.	MISSED APPROACH: Climb to 3100 on track 316° to JARAS and hold.
---	--

D-ATIS 135.1	NASHVILLE APP CON 118.4 360.7	NASHVILLE TOWER 118.6 257.8	GND CON 121.9 348.6	CLNC DEL 126.05	CPDLC
-----------------	----------------------------------	--------------------------------	------------------------	--------------------	-------

MISSED APCH FIX

4 NM

JARAS

36°

316°

△ 1208

△ 1035

△ 816

316° (10.6)

845

729

△ 770

△ 711

△ 717

△ 705

RW31

(IF) GILME
5000 210K
(RF REQD)

1029

4000

36°

(4.4)

USISE
4000

3500

(2.4)

(IF) BGEDD
4000 210K
(RF REQD)

3500

082°

(3.3)

NEZRU

2600

(2.7)

ZEDEM

1700

316°

(2.7)

(FAF) COVBI

1700

(3.8)

TIBVE

2800

228°

(4)

(IF) MUGEE
4000 210K
(RNP 0.50)
(RF REQD)

2500

316°

(5.8)

MSA RW31 25 NM

RADAR REQUIRED

(IF)
ONUGA
4000
(RNP 0.50)

3100

316°

JARAS

See planview for multiple IF locations.

COVBI

1700

RW31

3.4 NM

1700

GP 3.00°
TCH 52

CATEGORY	A	B	C	D
RNP 0.25 DA	1025-1½	447 (500-1½)		
RNP 0.30 DA	1099-1¾	521 (600-1¾)		

AUTHORIZATION REQUIRED