

Remarks	
6	
06	Nil
24	Nil

**EDLP AD 2.14 Approach and runway lighting**

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
06	ALSAF LIL_LIH 720 m Sequence flash available	G LIH	3.0° 41.00 ft	-	Up to 1280 m: W LIH, 1280 – 1880 m: R/W LIH, 1880 – 2180 m: R LIH. 15 m spacing	W LIH	R LIH	-
24	ALSAF LIL_LIH 900 m Sequence flash available	G LIH	3.0° 60.00 ft	-	Up to 1280 m: W LIH, 1280 – 1880 m: R/W LIH, 1880 – 2180 m: R LIH. 15 m spacing	W LIH	R LIH	-

Remarks	
10	
06	LED Lights for RWY CTR Line, RWY Edge Lights and THR Lights in use.
24	LED Lights for RWY CTR Line, RWY Edge Lights and THR Lights in use.

**EDLP AD 2.15 Other lighting, secondary power supply**

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDLP 2-5 LDI/WDI on the signal area 150 m NNE TWR
3	TWY edge and centre line LGT	TWY edge lights of TWYs A, A1, B, C, D, G, H, L, M: B LIL
4	Secondary power supply including switch-over time	Available/0 SEC
5	Remarks	Nil

**EDLP AD 2.16 Helicopter landing area**

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	Not specified; as instructed by TWR