

Type of aid MAG VAR Type of supported OPS VOR/ILS/MLS declination	ID	Frequency/ Channel service provider RPI	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Service volume radius GBAS	Remarks
1	2	3	4	5	6	7	8
Erfurt ILS 27 (CAT III) LOC (3° E/2020)	IERW	109.90 MHz	H24	N 50 58 53.81 E 010 56 07.86		-	Usable: Up to 10.6 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 2360 ft MSL. From 10.6 NM to 17 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 3000 ft MSL. From 17 NM to 25 NM in the area 010°(L)/ 010°(R) in relation to RCL MIN interception altitude: 3000 ft MSL.
GP	-	333.80 MHz	H24	N 50 58 48.79 E 010 58 12.00		-	
DME	IERW	CH36x (109.90 MHz *)	H24	N 50 58 48.77 E 010 58 11.96	1018	-	* Ghost frequency
Erfurt DME	EFD	CH57y (112.05 MHz *)	H24	N 50 58 57.40 E 010 57 27.79	1075	-	Operational coverage sector 0°–360°: 25 NM, 10000 ft MSL * Ghost frequency