

TABULAR DESCRIPTION**ILS Z RWY35 – Instrument Approach Procedure**

RNAV to ILS TRANSITION – APPROACH FROM DIXER											
Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (m)	Navigation Specification (1)
010	IF	DIXER	-	-	-	-	-	+6000	-	-	RNAV1/ RNP1
020	TF	SOROP	-	353° (355.6°)	-	9.1	-	+3000	-200	-	RNAV1/ RNP1
RNAV to ILS TRANSITION – APPROACH FROM UNDAF											
Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (m)	Navigation Specification (1)
010	IF	UNDAF	-	-	-	-	-	+5000	-	-	RNAV1/ RNP1
020	TF	SOROP	-	075° (077.6°)	-	7.3	-	+3000	-200	-	RNAV1/ RNP1
RNAV to ILS TRANSITION – APPROACH FROM UVNIB											
Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (m)	Navigation Specification (1)
010	IF	UVNIB	-	-	-	-	-	+5000	-	-	RNAV1/ RNP1
020	TF	SOROP	-	268° (270.9°)	-	10.2	-	+3000	-200	-	RNAV1/ RNP1
RNAV to ILS TRANSITION – APPROACH FROM VOG											
Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (m)	Navigation Specification (1)
010	IF	VOG	-	-	-	-	-	+FL100	-	-	RNAV1/ RNP1
020	TF	ML707	-	039° (041.5°)	-	9.0	-	+6000	-	-	RNAV1/ RNP1
030	TF	SOROP	-	039° (041.4°)	-	12.2	-	+3000	-200	-	RNAV1/ RNP1
ILS to RNAV TRANSITION – MISSED APPROACH											
Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (m)	Navigation Specification (1)
10	CF	ML704	Y	353° (355.7°)	2.9°E	-	-	+1000	-210		RNAV1/ RNP1
020	DF	TUCOZ	-	-	2.9°E	-	R	+3000	-210		RNAV1/ RNP1
030	HM	TUCOZ	Y	283 (286.1)	-	-	R	+3000	-210		RNAV1/ RNP1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	DIXER	353 (356.0)	3.5	-/4.7	R	+6000	-	-200	2.9 E	RNAV 1
HM	TUCOZ	283 (286.1)	3.7	1/-	R	+3000	-	-210	2.9 E	RNAV 1
HM	UNDAP	167 (170.0)	3.9	1/-	R	+5000	-	-210	2.9 E	RNAV 1
HM	UVNIB	318 (321.0)	5.3	1/-	L	+5000	-	-	2.9 E	RNAV 1
HM	VOG	350 (353.0)	4.3	-/6.3	L	+FL100	-	-	2.9 E	RNAV 1

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation RNAV.
(2) RNAV system with holding functionality.
(3) RNAV system without holding functionality.

WAYPOINT LIST

Waypoint Identifier	Coordinates
ML704	45°30'10.92"N 009°16'14.93"E
ML707	45°04'36.83"N 009°06'37.00"E