

HAMBURG-FINKENWERDER

INSTRUMENT APPROACH PROCEDURE

RNAV ILS RWY 05

TABULAR DESCRIPTION

Approach Segment	Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from BOGMU	IF	BOGMU	N 53 58 45.00 E 010 17 19.66	-	-	-	-	F110-A4000+	-	-	RNAV-1	-
	TF	HI225	N 53 42 47.20 E 010 22 36.13	-	(T168.9) 165	16.3	-	-	@220	-	RNAV-1	-
	TF	HI226	N 53 40 14.90 E 010 17 24.37	-	(T230.6) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI227	N 53 37 42.37 E 010 12 13.21	-	(T230.5) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI228	N 53 35 09.63 E 010 07 02.67	-	(T230.4) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI229	N 53 32 36.66 E 010 01 52.74	-	(T230.4) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI230	N 53 30 03.46 E 009 56 43.41	-	(T230.3) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI231	N 53 27 30.05 E 009 51 34.69	-	(T230.2) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI232	N 53 24 56.41 E 009 46 26.58	-	(T230.2) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI233	N 53 22 22.56 E 009 41 19.07	-	(T230.1) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI234	N 53 19 48.48 E 009 36 12.17	-	(T230.0) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI235	N 53 17 14.56 E 009 31 06.62	-	(T230.0) 226	4.0	-	-	-	-	RNAV-1	-
TF	HI255	N 53 20 45.01 E 009 26 10.39	-	(T319.9) 316	4.6	-	A4000+	-	-	RNAV-1	-	
TF	HI256	N 53 23 30.28 E 009 31 57.80	-	(T051.5) 047	4.4	-	A3000+	-	-	RNAV-1	-	
Initial APCH from RARUP	IF	RARUP	N 53 38 30.49 E 010 40 37.20	-	-	-	-	F110-A4000+	-	-	RNAV-1	-
	TF	HI230	N 53 30 03.46 E 009 56 43.41	-	(T252.4) 248	27.5	-	-	@220	-	RNAV-1	-
	TF	HI231	N 53 27 30.05 E 009 51 34.69	-	(T230.2) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI232	N 53 24 56.41 E 009 46 26.58	-	(T230.2) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI233	N 53 22 22.56 E 009 41 19.07	-	(T230.1) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI234	N 53 19 48.48 E 009 36 12.17	-	(T230.0) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI235	N 53 17 14.56 E 009 31 06.62	-	(T230.0) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI255	N 53 20 45.01 E 009 26 10.39	-	(T319.9) 316	4.6	-	A4000+	-	-	RNAV-1	-
TF	HI256	N 53 23 30.28 E 009 31 57.80	-	(T051.5) 047	4.4	-	A3000+	-	-	RNAV-1	-	
Initial APCH from NOLGO	IF	NOLGO	N 53 23 48.71 E 010 08 18.03	-	-	-	-	F110-A4000+	-	-	RNAV-1	-
	TF	HI230	N 53 30 03.46 E 009 56 43.41	-	(T312.2) 308	9.3	-	-	@220	-	RNAV-1	-
	TF	HI231	N 53 27 30.05 E 009 51 34.69	-	(T230.2) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI232	N 53 24 56.41 E 009 46 26.58	-	(T230.2) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI233	N 53 22 22.56 E 009 41 19.07	-	(T230.1) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI234	N 53 19 48.48 E 009 36 12.17	-	(T230.0) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI235	N 53 17 14.56 E 009 31 06.62	-	(T230.0) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI255	N 53 20 45.01 E 009 26 10.39	-	(T319.9) 316	4.6	-	A4000+	-	-	RNAV-1	-
TF	HI256	N 53 23 30.28 E 009 31 57.80	-	(T051.5) 047	4.4	-	A3000+	-	-	RNAV-1	-	
Initial APCH from RIBSO	IF	RIBSO	N 53 48 45.96 E 009 20 24.80	-	-	-	-	F110-A4000+	-	-	RNAV-1	-
	TF	HI210	N 53 45 05.42 E 009 29 40.41	-	(T123.8) 120	6.6	-	-	-	-	RNAV-1	-
	TF	HI211	N 53 41 46.45 E 009 25 55.25	-	(T213.9) 210	4.0	-	-	@220	-	RNAV-1	-
	TF	HI213	N 53 30 01.52 E 009 30 34.35	-	(T166.7) 162	12.1	-	-	-	-	RNAV-1	-
	TF	HI214	N 53 27 27.00 E 009 25 27.19	-	(T229.9) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI215	N 53 24 52.34 E 009 20 20.78	-	(T229.8) 226	4.0	-	-	-	-	RNAV-1	-
	TF	HI255	N 53 20 45.01 E 009 26 10.39	-	(T139.8) 136	5.4	-	A4000+	-	-	RNAV-1	-
	TF	HI256	N 53 23 30.28 E 009 31 57.80	-	(T051.5) 047	4.4	-	A3000+	-	-	RNAV-1	-

RNAV HOLDING IDENTIFICATION

Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	BOGMU	N 53 58 45.00 E 010 17 19.66	(T231.8) 227	230-	A4000+/FL110-	1 MIN	R	-
HM	RARUP	N 53 38 30.49 E 010 40 37.20	(T278.7) 274	230-	A4000+/FL110-	1 MIN	R	-
HM	NOLGO	N 53 23 48.71 E 010 08 18.03	(T007.9) 004	230-	A4000+/FL110-	1 MIN	L	-
HM	RIBSO	N 53 48 45.96 E 009 20 24.80	(T030.6) 026	230-	A4000+/FL110-	1 MIN	R	-