

Type of aid MAG VAR Type of supported OPS VOR/ILS/MLS declination	ID	Frequency/ Channel service provider RPI	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Service volume radius GBAS	Remarks
1	2	3	4	5	6	7	8
Muenster/Osnabrueck							
ILS 25 (CAT III) LOC (2° E/2022)	IMOW	110.10 MHz	H24	N 52 07 49.67 E 007 39 54.24		-	Usable: Up to 10 NM in the area 035°(L)/020°(R) in relation to RCL MIN interception altitude: 1550 ft MSL. From 10 NM to 17 NM in the area 035°(L)/ 020°(R) in relation to RCL MIN interception altitude: 2500 ft MSL. From 17 NM to 25 NM in the area 010°(L)/ 008°(R) in relation to RCL MIN interception altitude: 2500 ft MSL.
GP	-	334.40 MHz	H24	N 52 08 15.34 E 007 41 31.42		-	
DME	IMOW	CH38x (110.10 MHz *)	H24	N 52 08 15.34 E 007 41 31.42	169	-	* Ghost frequency
Muenster/Osnabrueck							
DME	MOD	CH87y (114.05 MHz *)	H24	N 52 08 16.69 E 007 41 14.07	200	-	Operational coverage sector 0°–360°: 25 NM, 10000 ft MSL DME unusable in sector 265°–315°: below <hr/> 0 – 25 NM 10000 ft MSL * Ghost frequency
Muenster/Osnabrueck							
NDB	MYN	371.00 KHz	H24	N 52 09 33.58 E 007 47 59.98		-	Operational range sector 0°–360°: 17 NM NDB unusable: in sector from station <hr/> 070°–090° 13 NM 090°–130° 17 NM 130°–180° 13 NM 180°–070° 17 NM 252°, 4.02 NM THR 25
Osnabrueck							
DVOR (1° E/2012)	OSN	114.30 MHz	H24	N 52 12 00.49 E 008 17 07.87		-	Operational coverage sector 023°–068°: 80 NM, 50000 ft MSL sector 068°–023°: 60 NM, 50000 ft MSL The DVOR may only be used for the radials in the published en-route, approach and departure procedures and is not permitted for area navigation.
Rekken							
DME	RKN	CH115x (116.80 MHz *)	H24	-	-	-	for further details see AIP NETHERLANDS * Ghost frequency