

WAAS CH 45944 W14A	APP CRS 140°	Rwy ldg 7301 TDZE 2585 Apt Elev 2592
--	------------------------	---

RNAV (GPS) RWY 14



DICKINSON/THEODORE ROOSEVELT RGNL (DIK)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 54°C.

MISSED APPROACH: Climb to 5000 direct LUFGI and hold.

ASOS 118.375	MINNEAPOLIS CENTER 124.25 236.825	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------



5 NM Holding Pattern LEGRY 6000 ← 320° 4400 ← 140° GP 3.00° TCH 50				5000 LUFGI	
AZIZO 4300 1.2 NM to RWY 14 RWY 14 5.5 NM 4 NM 1.2 NM					
CATEGORY	A	B	C	D	
LPV DA	2785- ³ / ₄ 200 (200- ³ / ₄)				
LNAV/VNAV DA	2835- ³ / ₄ 250 (300- ³ / ₄)				
LNAV MDA	3020-1	435 (500-1)	3020-1 ¹ / ₄	435 (500-1 ¹ / ₄)	
CIRCLING	3060-1	468 (500-1)	3120-1 ¹ / ₂ 528 (600-1 ¹ / ₂)	3200-2 608 (700-2)	