

ETSI AD 2.13 Declared Distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
06R	2940	3264	3183	2940	NIL
24L	2940	3264	3251	2940	NIL
06L	2439	2439	2439	2439	NIL
24R	2439	2439	2439	2439	NIL

ETSI AD 2.14 Approach and Runway Lighting

RWY Designator	APCH LGT type length INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT length	RWY Centre Line LGT length spacing colour INTST	RWY Edge LGT length spacing colour INTST	RWY End LGT colour WBAR	SWY LGT length colour	Remarks
1	2	3	4	5	6	7	8	9	10
06R	NATO-standard White LIH AFLS	Green	PAPI 3.0°	Not available	2940 m 15 m white red/ white red	2940 m 60 m White LIH	red	300 m red	NIL
24L	NATO-standard White LIH AFLS	Green	PAPI 3.0°	900 m	2940 m 15 m white red/ white red	2940 m 60 m White LIH	red	300 m red	NIL
06L	Modified Calvert system White LIH	Green	PAPI 3.0°	Not available	Not available	2940 m 60 m White LIH	red	Not available	NIL
24R	Modified Calvert system White LIH	Green	PAPI 3.0°	Not available	Not available	2940 m 60 m White LIH	red	Not available	NIL

ETSI AD 2.15 Other Lighting, Secondary Power Supply

1	ABN/IBN location, characteristics and hours of operation	ABN: white / green, on TWR
2	LDI location and LGT Anemometer location and LGT	LDI: Available, lighted
3	TWY edge and centre line lighting	Blue, LIL
4	Secondary power supply/switch-over time	Available / 15 Sec
5	Remarks	Obstruction marking and lighting available.