

Remarks	
10	
04	THR flashing lights only.
22	THR flashing lights only.

**EDMO AD 2.15 Other lighting, secondary power supply**

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR, HX
2	LDI location and LGT Anemometer location and LGT	-
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL
4	Secondary power supply including switch-over time	Available
5	Remarks	Landing T and wind sock lighted, signal area not lighted. TWY A southern part and TWY C, aprons General Atomics and DLR are not lighted.

**EDMO AD 2.16 Helicopter landing area**

1	Coordinates TLOF or THR of FATO Geoid undulation	W RWY 04/22
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	10 x 10 m, ASPH, 25 t, day marking
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	Nil

**EDMO AD 2.17 ATS airspace**

1	Designation and lateral limits	CTR Oberpfaffenhofen
2	Vertical limits	3500 ft MSL
3	Airspace classification	D
4	ATS unit call sign Language(s)	OBERPFAFFENHOFEN TOWER English, German
5	Transition altitude	5000 ft MSL
6	Hours of applicability	NIL
7	Remarks	For detailed airspace description see ENR 2.1

**EDMO AD 2.18 ATS communication facilities**

Service designation	Call sign	Channel/ Frequency (MHZ)	Sat-voice	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
ATIS	OBERPFAFFENHOFEN ATIS	126.580	-	-	HX	Designated operational coverage 50 NM, FL 200
APP	MUENCHEN RADAR (South)	127.955	-	-	HX	
TWR	OBERPFAFFENHOFEN TOWER	119.555	-	-	HX	Designated operational coverage 25 NM, 4000 ft AMSL