

STAR RNP 1/RNAV 1 RWY 35 DESCRIPTION

REMARK

1) For "monitoring and alerting" reason, RNP1 specification is required in case of radar service unavailability or degradation

TABULAR DESCRIPTION

ARBUM 1T

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ARBUM	N	-	-	-	-	-	-	RNAV 1 RNP 1 (1)
TF	LMT	N	132 (135.9)	-	31.2	-	+TRL	-	RNAV 1 RNP 1 (1)
TF	BC621	N	100 (103.2)	-	31.2	-	+TRL	-	RNAV 1 RNP 1 (1)
TF	RIROX	N	075 (078.8)	-	9.5	-	+3500	-	RNAV 1 RNP 1 (1)

BAGIX 1T

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BAGIX	N	-	-	-	-	-	-	RNAV 1 RNP 1 (1)
TF	BC684	N	094(097.9)	-	3.4	-	+FL110	-	RNAV 1 RNP 1 (1)
TF	LMT	N	094 (097.9)	-	33.2	-	+TRL	-	RNAV 1 RNP 1 (1)
TF	BC621	N	100 (103.2)	-	31.2	-	+TRL	-	RNAV 1 RNP 1 (1)
TF	RIROX	N	075 (078.8)	-	9.5	-	+3500	-	RNAV 1 RNP 1 (1)

CDC 1T

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	CDC	N	-	-	-	-	-	-	RNAV 1 RNP 1 (1)
TF	BC626	N	085(088.2)	-	20.1	-	+FL100	-	RNAV 1 RNP 1 (1)
TF	RIROX	N	075 (078.8)	-	15.0	-	+3500	-	RNAV 1 RNP 1 (1)

ADREN 1T

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ADREN	N	-	-	-	-	-	-	RNAV 1 RNP 1 (1)
TF	BC625	N	278(281.7)	-	10.7	-	+FL110	-	RNAV 1 RNP 1 (1)
TF	UVREF	N	255 (259.2)	-	12.0	-	+4000	-	RNAV 1 RNP 1 (1)

GEMVI 1T

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMVI	N	-	-	-	-	-	-	RNAV 1 RNP 1 (1)
TF	BC625	N	220(223.9)	-	19.8	-	+FL110	-	RNAV 1 RNP 1 (1)
TF	UVREF	N	255 (259.2)	-	12.0	-	+4000	-	RNAV 1 RNP 1 (1)

HOLDING RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM (4)	RIROX	075 (079)	3.6	1/-	R	+3500	-6000 (3)	-200	4.0 E	RNAV 1
HM (4)	UVREF	235 (239.0)	3.6	1/-	R	+4000	-6000 (3)	-200	4.0 E	RNAV 1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

(3) MAX HLD 6000FT to remain inside controlled airspace.

(4) direct entry only.

WAYPOINT LIST

Waypoint Identifier	Coordinates
BC621	38°47'0.43"N - 016°54'47.90"E
BC625	38°52'27.70"N - 017°30'42.03"E
BC626	38°45'55.82"N - 016°47'51.50"E
BC684	38°58'56.39"N - 015°33'51.03"E