

**ILS – Z RWY 21 – Instrument approach procedure****TABULAR DESCRIPTION****ILS/LOC transition to RNAV missed approach**

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH	Navigation Specification
010	CA	-	-	210 (212.6)	2.4 E	-	-	+1700	-190	-	RNP1
020	DF	MZ706	-	-	-	-	L	+4000	-190	-	RNP1
030	TF	MZ707	-	013 (015.3)	-	4.4	-	-	-190	-	RNP1
040	TF	TOPRU	-	300 (302.8)	-	5.0	L	+4000	-190	-	RNP1
050	HM	TOPRU	-	196 (198.0)	2.4 E	-	R	+4000	-185	-	RNAV1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	TOPRU	196 (198.0)	3.4	- / 4.2	R	+4000	-FL90 (3)	-185	2.4 E	RNAV1

**REMARK**

- (1) RNAV system with holding functionality  
(2) RNAV system without holding functionality  
(3) Higher level ATC discretion

**WAYPOINT LIST**

Waypoint Identifier	Coordinates
MZ706	44°34'45.93" N 007°49'37.01" E
MZ707	44°39'02.56" N 007°51'15.53" E