

EDDE AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	NIL
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDDE 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL TWY Center line lights of TWYs A, B, E, F: G LIH , Y/G LIH for exit from RWY onto TWY TWY Center line lights of TWY S: G LIH
4	Secondary power supply including switch-over time	Available / 1 SEC
5	Remarks	APRON 1: Retroreflective markers: B

EDDE AD 2.16 Helicopter landing area

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	TLOF HELIPAD D Surface: ASPH Strength: 39/F/B/X/T Markings: W FATO HELIPAD D Dimension: 25 x 25 m Surface: ASPH Strength: 39/F/B/X/T
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	TouchDownLiftOffLightSystem HELIPAD D W / LIH
7	Remarks	TWY D

EDDE AD 2.17 ATS airspace

1	Designation and lateral limits	CTR Erfurt
2	Vertical limits	3500 ft MSL
3	Airspace classification	D
4	ATS unit call sign Language(s)	ERFURT TOWER English, German
5	Transition altitude	5000 ft MSL
6	Hours of applicability	NIL
7	Remarks	For detailed airspace description see ENR 2.1