

RNP RWY 01 TABULAR DESCRIPTION

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA (°)/TCH (ft)	Navigation Specification
010	IF	PRU	-	-	-	-	-	+6000	-	-	RNP APCH
020	TF	RZ507	-	212° (215.3°)	-	13.6	-	-	200	-	RNP APCH
030	TF	RZ508	-	191° (194.2°)	-	3.0	-	+4900	200	-	RNP APCH
040	TF	RZ503	-	101° (104.2°)	-	5.0	L	+4900	200	-	RNP APCH
050	TF	DERUX	-	011° (014.3°)	-	5.0	L	+3100	200	-	RNP APCH
010	IF	DERUX	-	-	-	-	-	+5500	-	-	RNP APCH
020	TF	RZ501	-	101° (104.3°)	-	5.0	-	+5500	200	-	RNP APCH
030	TF	RZ502	-	191° (194.4°)	-	5.0	R	+5500	200	-	RNP APCH
040	TF	RZ503	-	281° (284.4°)	-	5.0	R	+4900	200	-	RNP APCH
050	TF	DERUX	-	011° (014.3°)	-	5.0	R	+3100	200	-	RNP APCH
010	TF	DERUX	-	-	-	-	-	+3100	200	-	RNP APCH
020	TF	RZ515	-	011° (014.3°)	-	3.3	-	+3100	-	-	RNP APCH
030	TF	RWY01	Y	011° (014.4°)	-	6.6	-	@717 (3)	-	-3.4/50	RNP APCH
040	CA	-	-	011° (014.4°)	-	-	-	+1350	160	-	RNP APCH
050	CF	RETKU	-	246° (249.6°)	-	-	L	+4500	160	-	RNP APCH
060	HM	RETKU	Y	246° (249.6°)	-	-	R	+4500	185	-	RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	PRU	178° (181°)	3.7	- / 4.9	R	6000	-	200	3.0	RNAV 1
HM	DERUX	011° (014°)	3.4	- / 4.3	R	5500	FL80	185	3.0	RNAV 1
HM	RETKU (4)	246° (249°)	3.4	- / 4.3	R	4500	5500	185	3.0	RNAV 1

- (1) RNAV system with holding functionality;
(2) RNAV system without holding functionality;
(3) THR Altitude plus TCH.
(4) Holding entry on track only

WAYPOINT LIST
RNP RWY 01

Waypoint Identifier	Coordinates
RZ501	42° 54' 30.38" N 012° 33' 54.29" E
RZ502	42° 49' 39.71" N 012° 32' 13.09" E
RZ503	42° 50' 53.91" N 012° 25' 38.05" E
RZ507	42° 55' 02.23" N 012° 20' 02.86" E
RZ508	42° 52' 07.73" N 012° 19' 02.76" E
RZ515	42° 58' 54.71" N 012° 28' 24.72" E