



CHG: radio data

**RNAV STAR RWY 25**

ARLON 1M NAXEP 1M OTKAP 1M VEHUF 1M

- DME/DME OPS: NOT SUPPORTED
- ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART  
ATC WILL GIVE DESCENT CLEARANCES
- WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS  
PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC
- CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR
- NOISE ABATEMENT: AVOID OVERFLYING THE CITY OF KOUVOLA BELOW 2000

- RCF: SELECT TRANSPONDER CODE 7600
- RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:  
FOLLOW THE STAR TO THE RESPECTIVE RWY AND  
EXECUTE IAP AND LAND
- DURING RADAR VECTURING BEFORE IAF:  
IN ACCORDANCE WITH THE RULES OF THE AIR
- AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

EFUT RNAV STAR RWY 25										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
ARLOM 1M RNAV 1	010	IF	ARLOM	-	-	-	-	F100+		
	020	TF	RURET	-	291°	301.2°T	16.2	A2300+		

NAXEP 1M RNAV 1	010	IF	NAXEP	-	-	-	-	F100+		
	020	TF	TOWZU	-	091°	101.5°T	6.8			
	030	TF	POWUQ	-	067°	077.4°T	4.0			
	040	TF	EPATU	-	068°	078.0°T	9.6	A2300+		K240-
	050	TF	RURET	-	158°	168.3°T	5.0	A2300+		

OTKAP 1M RNAV 1	010	IF	OTKAP	-	-	-	-	F100+		
	020	TF	RURET	-	193°	203.1°T	9.8	A2300+		

VEHUF 1M RNAV 1	010	IF	VEHUF	-	-	-	-	F100+		
	020	TF	ATVAP	-	078°	087.9°T	15.3			
	030	TF	ELSUW	-	068°	077.8°T	10.5			
	040	TF	AMGUX	-	068°	078.0°T	9.6	A2300+		K240-
	050	TF	RURET	-	338°	348.4°T	5.0	A2300+		

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM		
RURET	348.4°T	338°	Right	K230-	A2300	1 MIN	-		

WPT COORD
SEE PAGE EFUT AD 2.15 - 1