

EDQA AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
03	968	968	1104	935
21	935	935	1104	968

Remarks	
6	
03	Nil
21	Nil

EDQA AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
03	SALS LIH 420 m	G LIH	3.3°	-	Up to 550 m: W LIH; 550 - 800 m: R/W LIH; 800 - 1104 m: R LIH. 15 m spacing	Up to 169 m: R LIH; 169 - 1104 m: W LIH. 60 m spacing.	R LIH	-
21	SALS LIH 300 m	G LIH	3.8°	-	Up to 550 m: W LIH; 550 - 800 m: R/W LIH; 800 - 1104 m: R LIH. 15 m spacing	Up to 169 m: R LIH; 169 - 1104 m: W LIH. 60 m spacing.	R LIH	-

Remarks	
10	
03	Nil
21	Nil

EDQA AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	White/white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDQA 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL
4	Secondary power supply including switch-over time	Available/15 SEC
5	Remarks	Nil