

STAR RNAV 1/RNP1 RWY14 DESCRIPTION

ACMIZ 1R (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	ACMIZ	-	-	-	-	-	-	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

NEVNI 1R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	NEVNI	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	PO402	-	185 (188.1)	-	20.3	-	+FL110	-	RNAV 1/ RNP 1
TF	DREUX	-	185 (188.0)	-	3.9	-	-FL150 +6000	-210	RNAV 1/ RNP 1
TF	ADSAS	-	128 (131.5)	-	5.0	-	-FL150 +5000	-210	RNAV 1/ RNP 1
TF	NIPLI	-	042 (045.2)	-	6.9	-	+5000	-190	RNAV 1/ RNP 1
TF	ACMIZ	-	312 (315.1)	-	3.5	L	+5000	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

OSBUL 1R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	OSBUL	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	LAISH	-	347 (350.4)	-	13.4	-	+6000	-	RNAV 1/ RNP 1
TF	ADSAS	-	038 (041.4)	-	12.2	-	-FL150 +5000	-210	RNAV 1/ RNP 1
TF	NIPLI	-	042 (045.2)	-	6.9	-	+5000	-190	RNAV 1/ RNP 1
TF	ACMIZ	-	312 (315.1)	-	3.5	L	+5000	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

OSTEG 1R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	OSTEG	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	AIXBA	-	298 (300.8)	-	5.2	-	+6000	-	RNAV 1/ RNP 1
TF	UVNON	-	298 (300.7)	-	7.0	-	+6000	-	RNAV 1/ RNP 1
TF	INFRI	-	223 (225.7)	-	4.1	-	-FL200 +6000	-	RNAV 1/ RNP 1
TF	PO403	-	222 (225.6)	-	6.5	-	+5000	-210	RNAV 1/ RNP 1
TF	ELDIP	-	312 (315.2)	-	5.0	R	+5000	-190	RNAV 1/ RNP 1
TF	NIPLI	-	312 (315.1)	-	5.0	-	+5000	-190	RNAV 1/ RNP 1
TF	ACMIZ	-	312 (315.1)	-	3.5	-	+5000	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

TAFIQ 1R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	TAFIQ	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	PO406	-	215 (218.1)	-	6.4	-	+FL110	-	RNAV 1/ RNP 1
TF	PO401	-	215 (218.0)	-	3.0	-	+6000	-	RNAV 1/ RNP 1
TF	PO402	-	230 (232.8)	-	12.5	-	+6000	-	RNAV 1/ RNP 1
TF	DREUX	-	185 (188.0)	-	3.9	-	-FL150 +6000	-210	RNAV 1/ RNP 1
TF	ADSAS	-	128 (131.5)	-	5.0	-	-FL150 +5000	-210	RNAV 1/ RNP 1
TF	NIPLI	-	042 (045.2)	-	6.9	-	+5000	-190	RNAV 1/ RNP 1
TF	ACMIZ	-	312 (315.1)	-	3.5	L	+5000	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

TZO 1R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	TZO	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	EKDOG	-	112 (115.0)	-	23.0	-	+FL110	-	RNAV 1/ RNP 1
TF	DIRVU	-	112 (115.4)	-	11.1	-	+6000	-	RNAV 1/ RNP 1
TF	DREUX	-	128 (131.4)	-	6.0	-	-FL150 +6000	-210	RNAV 1/ RNP 1
TF	ADSAS	-	128 (131.5)	-	5.0	-	-FL150 +5000	-210	RNAV 1/ RNP 1
TF	NIPLI	-	042 (045.2)	-	6.9	-	+5000	-190	RNAV 1/ RNP 1
TF	ACMIZ	-	312 (315.1)	-	3.5	L	+5000	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

XUBKA 1R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification (4)
IF	XUBKA	-	-	-	-	-	-	-	RNAV 1/ RNP 1
TF	DIGTO	-	343 (346.3)	-	13.5	-	+6000	-	RNAV 1/ RNP 1
TF	INFRI	-	298 (300.8)	-	13.2	-	-FL200 +6000	-	RNAV 1/ RNP 1
TF	PO403	-	222 (225.6)	-	6.5	-	+5000	-210	RNAV 1/ RNP 1
TF	ELDIP	-	312 (315.2)	-	5.0	R	+5000	-190	RNAV 1/ RNP 1
TF	NIPLI	-	312 (315.1)	-	5.0	-	+5000	-190	RNAV 1/ RNP 1
TF	ACMIZ	-	312 (315.1)	-	3.5	-	+5000	-190	RNAV 1/ RNP 1
TF	PO425	-	295 (298.5)	-	17.7	-	+5000	-190	RNAV 1/ RNP 1
TF	EGFUV	-	312 (314.8)	-	6.4	-	+5000	-190	RNAV 1/ RNP 1

HOLDING RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(m in.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	ACMIZ	312 (315.1)	3.6	1/-	L	+4000	-	-200	3.1°E	RNAV 1
HM	ADSAS	128 (131.4)	4.0	- / 5.1	R	+5000	-	-210	3.1°E	RNAV1
HM	EGFUV	312 (314.8)	3.5	1/-	L	+5000	-	-190	3.1°E	RNAV 1
HM	ELDIP	312 (315.2)	4.0	- / 5.1	L	+5000	(3)	-210	3.1°E	RNAV1

REMARKS

- (1) for RNAV system with holding functionality
- (2) for RNAV system without holding functionality
- (3) Higher Altitude/Levels ATC Discretion
- (4) For "monitoring and alerting" reason, RNP1 specification is required in case of radar service unavailability or degradation

WAYPOINT LIST

Waypoint Identifier	Coordinates
PO401	45° 26' 24.40" N 010° 35' 23.18" E
PO402	45° 18' 50.55" N 010° 21' 18.85" E
PO403	45° 09' 29.70" N 010° 42' 48.51" E
PO406	45° 28' 46.25" N 010° 38' 00.66" E
PO425	45° 27' 30.08" N 010° 07' 10.62" E