

BIKF RNAV STAR RWY 19
Recommended Coding Tables

DEVUD 3K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	DEVUD	-		+11.3					RNAV 1 (GNSS)
020	TF	UNLOS	-	274 (263.2)	+11.8	24.2		F110+		RNAV 1 (GNSS)
030	TF	KF152	-	274 (262.3)	+12.1	15.5		A7000+		RNAV 1 (GNSS)
040	TF	KF157	-	274 (261.8)	+12.2	6.9		A5000+		RNAV 1 (GNSS)
050	TF	ELVUM	-	274 (261.6)	+12.3	6.0		A3000+	-220	RNAV 1 (GNSS)

NASBU 4K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	NASBU	-		+11.2					RNAV 1 (GNSS)
020	TF	KF383	-	285 (273.6)	+11.6	20.8		F130+		RNAV 1 (GNSS)
030	TF	TESGO	-	284 (272.9)	+11.8	9.0		F110+		RNAV 1 (GNSS)
040	TF	KF148	-	307 (294.9)	+12.1	14.7		A7000+		RNAV 1 (GNSS)
050	TF	KF149	-	306 (294.4)	+12.2	6.9		A5000+		RNAV 1 (GNSS)
060	TF	ELVUM	-	306 (294.2)	+12.3	6.0		A3000+	-220	RNAV 1 (GNSS)

ASRUN 3K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	ASRUN	-		+11.1					RNAV 1 (GNSS)
020	TF	KF156	-	308 (296.6)	+11.4	14.8		F150+		RNAV 1 (GNSS)
030	TF	RAVLA	-	320 (308.7)	+11.8	18.4		F110+		RNAV 1 (GNSS)
040	TF	KF158	-	320 (308.5)	+11.9	5.9		F100+		RNAV 1 (GNSS)
050	TF	KF159	-	320 (308.0)	+12.1	9.6		A7000+		RNAV 1 (GNSS)
060	TF	KF155	-	320 (307.8)	+12.2	7.7		A4500+		RNAV 1 (GNSS)
070	TF	ELVUM	-	335 (323.1)	+12.3	5.2		A3000+	-220	RNAV 1 (GNSS)

BASLU 3K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	BASLU	-		+11.4					RNAV 1 (GNSS)
020	TF	KF151	-	345 (333.5)	+11.8	29.6		F130+		RNAV 1 (GNSS)
030	TF	BETLU	-	345 (333.0)	+11.9	8.1		F110+		RNAV 1 (GNSS)
040	TF	KF244	-	345 (332.9)	+12.0	6.0		F100+		RNAV 1 (GNSS)
050	TF	KF154	-	345 (332.8)	+12.1	9.7		A7000+		RNAV 1 (GNSS)
060	TF	KF155	-	345 (332.7)	+12.2	7.6		A4500+		RNAV 1 (GNSS)
070	TF	ELVUM	-	335 (323.1)	+12.3	5.2		A3000+	-220	RNAV 1 (GNSS)

BIRNA 4K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	BIRNA	-		+13.0					RNAV 1 (GNSS)
020	TF	KF166	-	063 (050.5)	+12.8	19.2				RNAV 1 (GNSS)
030	TF	GARSU	-	047 (034.1)	+12.7	17.6				RNAV 1 (GNSS)
040	TF	VALUX	-	047 (034.5)	+12.5	28.3		A3000+	-220	RNAV 1 (GNSS)

ELDIS 4K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	ELDIS	-		+13.3					RNAV 1 (GNSS)
020	TF	NAPAT	-	073 (059.9)	+12.9	32.1				RNAV 1 (GNSS)
030	TF	VALUX	-	074 (060.8)	+12.5	27.9		A3000+	-220	RNAV 1 (GNSS)

GIRUG 4K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	GIRUG	-		+13.6					RNAV 1 (GNSS)
020	TF	KULUS	-	099 (085.6)	+13.1	26.6				RNAV 1 (GNSS)
030	TF	VALUX	-	100 (086.5)	+12.5	28.4		A3000+	-220	RNAV 1 (GNSS)

INGAN 4K

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	INGAN	-		+13.6					RNAV 1 (GNSS)
020	TF	RUVET	-	131 (117.7)	+13.1	22.4				RNAV 1 (GNSS)
030	TF	VALUX	-	131 (118.3)	+12.5	28.1		A3000+	-220	RNAV 1 (GNSS)