

RNAV TRANSITION TO ILS APPROACH via ABLID

Path Terminator	Waypoint identifier	Flyover	Course/Track °M (°T)	Turn Direction	Altitude Constraint (ft)	Speed Limit (kt)/Bank Angle	Recommended Navaid	Bearing/Range from Navaid	Distance from THR (NM)	Navigation Performance
IF	ABLID	-	-	-	+5000 ⁽¹⁾	210	-	-	21.2	RNAV 1
TF	GIVAT	-	042 (045.1)	-	+4000 ⁽¹⁾	200	-	-	16.2	RNAV 1
TF	ERMOB	-	042 (045.9)	-	+3000	-	-	-	12.2	RNAV 1

RNAV TRANSITION TO ILS APPROACH via BOLVO

Path Terminator	Waypoint identifier	Flyover	Course/Track °M (°T)	Turn Direction	Altitude Constraint (ft)	Speed Limit (kt)/Bank Angle	Recommended Navaid	Bearing/Range from Navaid	Distance from THR (NM)	Navigation Performance
IF	BOLVO	-	-	-	+5000 ⁽¹⁾	210	-	-	-	RNAV 1
TF	GIVAT	-	313 (315.9)	-	+4000 ⁽¹⁾	200	-	-	16.2	RNAV 1
TF	ERMOB	-	042 (045.9)	-	+3000	-	-	-	12.2	RNAV 1

RNAV TRANSITION TO ILS APPROACH via RIVEV

Path Terminator	Waypoint identifier	Flyover	Course/Track °M (°T)	Turn Direction	Altitude Constraint (ft)	Speed Limit (kt)/Bank Angle	Recommended Navaid	Bearing/Range from Navaid	Distance from THR (NM)	Navigation Performance
IF	RIVEV	-	-	-	+5000 ⁽¹⁾	210	-	-	-	RNAV 1
TF	GIVAT	-	133 (135.7)	-	+4000 ⁽¹⁾	200	-	-	16.2	RNAV 1
TF	ERMOB	-	042 (045.9)	-	+3000	-	-	-	12.2	RNAV 1

REMARKS

⁽¹⁾ 3000 FT ATC Discretion